



QT2 Device

The QT2 device takes the response experience to a new level of performance. Providing the same features as other RF clickers, the QT2 expands upon functionality by offering advanced capabilities such as a full QWERTY keypad and backlit screen for easy viewing. The QT2 provides the richest and most fulfilling response experience ever.

Specs

ENCLOSURE

Dimensions: 5.1" L x 2.98" W x .88" H - Grip Area .66 H (129mm L x 76mm W x 20mm H - Grip Area 16mm)
 Weight: 4.8 oz. (with batteries)
 Ergonomic, lightweight, compact format
 LCD screen with backlight for optimum viewing
 Durable casing
 Accommodation for a lanyard included

USER INPUT

QWERTY Entry 56 Keys, Plastic Keys with reliable Metal Dome buttons
 Laser etched graphics with Backlight
 512 character limit for text
 Supported Symbols . , ' " ; ! \ ? @ # \$ % ^ & * () _ + - = / < > [] { } ? € £

DISPLAY

57.1mm x 26.9mm viewable area
 Easy to read LCD Display
 Channel Number, Battery Life Indicator,
 Answer Choice, Response Confirmation

POWER & POWER MANAGEMENT

Two AAA batteries
 Average battery life is 6 to 12 months

USER IDENTIFICATION

Fixed device ID
 Setup is plug-and-play with TurningPoint

RF TECHNOLOGY

Up to 74 sessions can be running at one time in close proximity without interference
 Fully FCC, CE and Industry Canada certified
 Ability to prohibit audience from changing channel

RANGE

Presentation Mode - Range for one RF receiver is 200 feet (400 ft. coverage)
 Test Mode - Data is stored in nonvolatile memory until individual finishes test and uploads responses

SUPPORTED PRODUCTS

TurningPoint v.5.3 and higher
 TurningPoint Cloud
 Insight 360 v.2.3.2 and higher
 Flow v.1.7 and higher

SUPPORTED RECEIVERS

Storage
*Only supported with receiver firmware version 3.7+
 Standard
*Only supported with receiver firmware version 3.7+