



55" Ultra Narrow Bezel Video Wall Displays



PANEL

Size	55"
Brightness (Cd / M2)	700 cd/m2
Panel Type	24/7 TV Panel
Resolution	1920x1080
Orientation	Horizontal / Vertical
Contrast Ratio	1400 : 1
Dynamic Contrast Ratio	1M:1
Panel Life Time (Typ.)	60000hrs
Panel Life Time (Average)	50000hrs
Response Time	12 ms
Areas of Usage	Indoor
Backlight Type	DLED
Panel Technology	IPS
Front Type	Ultra narrow bezel
Active Area	1209.6(H) x 680.4(V)
Color Value	10Bit (D), 1.06 Billion colors
H-Freq	67,5 Khz
Max. Pixel Freq.	74.25 MHz
V-Freq	60 Hz

MAINBOARD

Mainboard Model	MB120DS
-----------------	---------

MONITOR CONNECTIVITY

RGB Input	Dsub 15 PIN VGA CON., YPbPr
RGB Output	N/A
Video Input	2xHDMI2.0, 1xUSB3.0, 1xUSB2.0
Video Output	HDMI2.0,
Audio Input	LINE IN JACK
Audio Output	LINE OUT JACK
External Control	RS232(DSUB 9P), RJ12, Ethernet
External Sensor	N/A

WORKING CONDITIONS

Temperature Conditions	+50°C / 0°C
Humidity	%90

POWER

Power Supply	110 VAC - 240 VAC
Power Consumption (Deep Standby)	0.5W<
Power Consumption (On Full Load)	220W

MECHANICAL FEATURES

Size	1213.4(H) x 684.2(V) x 52.5 / 112.1 (D)
Shipping Size	1359(H) x 804(V) x 209(D)
Weight (kg)	37 Kg
Shipping Weight (kg)	42.5 Kg
Vesa Mounting Size	400x600
Bezel Width	3.5 mm

FEATURES

Main Features	Videowall setup with Daisy-Chain, Open Content Management Support, Vsign Software, Manual Fine Color Calibration, Videowall Scheduler, Auto-Launch, Auto-switch on Failover, Panel Lock
Mechanical Features	ON/OFF Button, IR Extender, Carrying Handles
Speaker	N/A

ACCESSORY

Standard	QSG, Warranty Card, IB, Power Cord, Remote Control, RC Battery, Display Port Cable, USB to Rs232 Converter
OPS	N/A
Touch Overlay	N/A
Motorized Stand	Standard

CERTIFICATION

Safety	Yes
EMC	Yes
CB	Yes
S-Mark	Yes
CE	Yes