

VW55X503

VESTEL



55" Extra Thin Video Wall Displays



PANEL

Size	55"
Brightness (Cd / M2)	500 cd/m2
Panel Type	24/7 TV Panel
Resolution	1920x1080
Orientation	Horizontal / Vertical
Contrast Ratio	1400 : 1
Dynamic Contrast Ratio	1M:1
Panel Life Time (Typ.)	60000hrs
Panel Life Time (Average)	50000hrs
Response Time	8 ms
Areas of Usage	Indoor
Backlight Type	DLED
Panel Technology	IPS
Front Type	Extra narrow bezel
Active Area	1209.6(H) x 680.4(V)
Viewing Angle	178°
Color Value	10 bit(D), 1.06 Billion colors
H-Freq	67,5 KHz
Max. Pixel Freq.	74.25 MHz
V-Freq	60 Hz

MAINBOARD

Mainboard Model	MB120DS
-----------------	---------

MONITOR CONNECTIVITY

RGB Input	Dsub 15 PIN VGA CON., YPbPr
RGB Output	N/A
Video Input	2xHDMI2.0, DP1.2a, DVI, 1xUSB3.0, 1xUSB2.0
Video Output	DP1.2a
Audio Input	LINE IN JACK
Audio Output	LINE OUT JACK
External Control	RS232(DSUB 9P), RJ12, Ethernet
External Sensor	N/A

WORKING CONDITIONS

Temperature Conditions	+50°C / 0°C
Humidity	%90

POWER

Power Supply	110 VAC - 240 VAC
Power Consumption (Deep Standby)	0.5W<
Power Consumption (On Full Load)	140W

MECHANICAL FEATURES

Size	1211.4 (L) x 682.3 (H) x 54.1 / 104.6(D)
Shipping Size	1359(H) x 804(V) x 209(D)
Weight (kg)	30.50 kg
Shipping Weight (kg)	36 Kg
Vesa Mounting Size	400x600
Bezel Width	1.8 mm

FEATURES

Main Features	Videowall setup with Daisy-Chain, Open Content Management Support, Vsign Software, Manual Fine Color Calibration, Videowall Scheduler, Auto-Launch, Auto-switch on Failover, Panel Lock
Mechanical Features	ON/OFF Button, IR Extender, Carrying Handles
Speaker	N/A

ACCESSORY

Standard	QSG, Warranty Card, IB, Power Cord, Remote Control, RC Battery, Display Port Cable, USB to Rs232 Converter
OPS	N/A
Touch Overlay	N/A
Mounting Kit	Standard

CERTIFICATION

Safety	Yes
EMC	Yes
CB	Yes
S-Mark	Yes
CE	Yes